



UNIXX PROFESSIONAL FORMULA 5W-40 FULLY SYNTHETIC ENGINE OIL

August 16 2017

Product Description

Unixx Professional Formula 5W-40 Fully Synthetic engine oil uses a high viscosity index synthetic base oil, fortified with a special blend of premium additives to deliver unsurpassed wear protection to keep your engine in peak condition.

It is uniquely designed to improve engine performance under high temperatures and actively clean and remove engine deposits and sludge for optimal performance, even under extended oil change intervals. The oil is highly stable, providing excellent resistance to oil degradation^{oo} and exceptional protection against wear.

Benefits

- Excellent high and low temperature performance
- Enhanced frictional properties to protect against engine wear and corrosion
- Removes and prevents engine deposits and sludge build up
- Highly resistant to oil degradation resulting in extended oil change intervals

Performance Standards

Unixx Professional Formula 5W-40 is suitable for all new and high performance cars. It meets or exceeds:

API SN/SM/CF	MB 229.3
ACEA A3/B3/B4	VW 502 00/505 00
PORSCHE A40	RN710/700
BMW LL-01	

Typical Properties

Description	Unit	Test Instrument	Unixx Professional Formula 5W-40
Density @30°C	g/cm3	ASTM D4052	0.8456
Kinematic Viscosity @ 40°C	mm2/s	ASTM D445	87.58
Kinematic Viscosity @ 100°C	mm2/s	ASTM D445	14.42
Viscosity Index	-	ASTM D2270	172
Flash Point by COC°C	Deg C	ASTM D92	250
Pour Pont °C	Deg C	ASTM D5950/D6892	-27
Total Base Number	mgKOH/g	ASTM D2896	9.18

Typical physical and chemical characteristics do not constitute as specifications. Contix Asia Pte. Ltd. reserves the right to amend and change the information herein without notification as a result of continual product research and development