



UNIXX PERFORMANCE FORMULA 10W-40 SYNTHETIC BLEND ENGINE OIL

August 16 2017

Product Description

Unixx Performance Formula 10W-40 engine oil uses a Hydro clear base oil which has high thermal stability and superior resistance to oil degradation. It has excellent oxidation stability, extending the life of the oil. Our additive formulation provides good wear and corrosion protection. It is extremely effective in cleaning and preventing engine deposit and sludge build-up for a more responsive engine.

Benefits

- Advanced additive formulation reduces engine deposits and sludge build-up for more efficient engine performance.
- Excellent wear and corrosion protection.
- Hydro clear base oil provide superior resistance to oil degradation even at high operating temperatures.
- Exceptional oxidation stability extends oil life.

Performance Standards

Unixx Performance Formula 10W-40 is a high quality performance lubricant suitable for all new modern day cars requiring API SN/CF

Typical Properties

Description	Unit	Test Instrument	Unixx Performance Formula 10W-40
Density @30°C	g/cm ³	ASTM D4052	0.8574
Kinematic Viscosity @ 40°C	mm ² /s	ASTM D445	101.2
Kinematic Viscosity @ 100°C	mm ² /s	ASTM D445	14.71
Viscosity Index	-	ASTM D2270	151
Flash Point by COC°C	Deg C	ASTM D92	240
Pour Point °C	Deg C	ASTM D5950/D6892	-30
Total Base Number	mgKOH/g	ASTM D2896	7.43

Typical physical and chemical characteristics do not constitute as specifications. Contix Asia Pte. Ltd. reserves the right to amend and change the information herein without notification as a result of continual product research and development