



UNIXX RACING FORMULA 5W-50 FULLY SYNTHETIC ENGINE OIL

August 16 2017

Product Description

Unifix Racing Formula 5W-50 is an extra high performance synthetic engine oil designed for a wide range of high output engines. Using revolutionary technology and formulated with specially selected synthetic base stocks and advanced additives system, Unifix Racing Formula oils meets the latest industry standards for excellent performance in turbo-charged and multi-valves engines. It is particularly suited for racing enthusiasts looking to push their cars through extreme operating conditions.

Unifix Racing Formula 5W-50 is a highly shear-stable multi-grade viscosity lubricants with excellent oxidation and thermal stability. Designed for severe operating conditions it is perfectly adapted to gasoline engine vehicles equipped with catalytic converters.

Benefits

- Surpasses the warranty service requirements for a wide range of engines
- Superior all-round wear protection
- Reduced maintenance costs by optimizing oil drain and engine overhaul intervals
- Excellent sludge and varnish deposit control
- Outstanding engine cleanliness
- Low oil consumption
- Smoother power transmission
- Excellent low temperature pumpability and high temperature stability

Applications

- Recommended for a wide range current US, European engines as well as Japanese and Korean models in all service condition.
- Suitable for passenger cars, MPVs, SUVs and force-induction gasoline engines.
- Also suitable for all high-rev engine designs for which API SN performance oils are specified.

Performance Standards

- API SN
- ACEA A5/B5
- MB p229.3
- VW 502 00/505 00
- GM LL-A-025
- GM LL-B-025



Typical Properties

Description	Unit	Test Instrument	Unifix Racing Formula 5W-50
Density, kg/Litre @ 15°C	g/cm ³	ASTM D4052	0.867
Appearance			Clear
Kinematic Viscosity, mm ² /s @ 40°C	mm ² /s	ASTM D445	112.9
Kinematic Viscosity, mm ² /s @ 100°C	mm ² /s	ASTM D445	17.5
Viscosity Index		ASTM D2270	171
Flash Point COC, °C	Deg C	ASTM D92	230
Pour Point, °C	Deg C	ASTM D5950/D6892	-36
Total Base Number	mgKOH/g	ASTM D2896	8.2

Typical physical and chemical characteristics do not constitute as specifications. Contix Asia Pte. Ltd. reserves the right to amend and change the information herein without notification as a result of continual product research and development