



**UNIXX RACING FORMULA SERIES with PAO
PREMIUM FULLY SYNTHETIC ENGINE OIL**

Dec 3, 2017

PRODUCT DESCRIPTION

Unixx Racing Formula is a series of Premium Fully Synthetic Engine Oil in a variety of viscosities. It is formulated with a combination of PAO (Polyalphaolefins) and molecular converted synthetic base stocks making it extremely shear stable. It is designed for a wide range of high output engines and meets the latest industry standards for excellent performance.

Premium performance enhancing additives are incorporated for outstanding thermal stability, improved viscosity-temperature characteristics and excellent low temperature fluidity. It is also supplemented with a special friction modifier. The synergistic performance derived from carefully chosen synthetic base stocks and additives package, ensure unsurpassed protection against wear, deposits, varnish, rust and corrosion, and excellent fuel economy.

Unixx Racing Formula is recommended for a wide range of heavy-duty applications and operating environments. It is even designed for use in the latest turbo-charged 4-stroke engines.

BENEFITS

- Surpasses the warranty service requirements for a wide range of engines
- Maintains excellent control of oil consumption
- Excellent sludge and varnish deposit control
- Outstanding engine cleanliness
- Reduces maintenance costs by maximizing oil drain and engine overhaul periods
- Smoother power transmission
- Protects against rust and corrosion
- Excellent fuel economy

APPLICATIONS

- Recommended for a wide range of current US, European engines as well as Japanese and Korean models.
- Suitable for passenger cars, SUVs, MPVs, light-duty diesel engines and turbo-charged vehicles.
- Also suitable for the high-rev engine designs for which API SN/CF performance oils are specified.

PERFORMANCE STANDARDS

Unixx Racing Formula engine oils meet and/or exceed multiple industry and engine manufacturer's standards and can be used on both gasoline and diesel engines.

- API SN
- ACEA A3/B3; A3/B4
- ILSAC GF-3/GF-4
- MB p229.5
- Porsche A40
- VW 502.00/505.00



TYPICAL PROPERTIES

SAE Grade	Unixx Racing Formula 0W-20	Unixx Racing Formula 0W-30W	Unixx Racing Formula 0W-40
Density, kg / Litre @ 15°C	0.840	0.846	0.857
Appearance	Clear	Clear	Clear
Kinematic Viscosity, mm ² /s @ 40°C	46.55	61.35	72.15
Kinematic Viscosity, mm ² /s @ 100°C	8.70	11.20	13.1
Viscosity Index	169	179	186
Brookfield Viscosity, cP @ -35°C	5300	5850	
Brookfield Viscosity, cP @ -30°C			5525
Pour Point, °C	-42	-50	-45
Flash Point COC, °C	230	226	220

Typical physical and chemical characteristics do not constitute as specifications. Contix Asia Pte. Ltd. reserves the right to amend and change the information herein without notification as a result of continual product research and development